

TECHNICAL DATASHEET

TIMKEN INDUCTION HEATER

VHIS-G2-75

- Heating capacity up to 100 kg (workpiece weight)
- Available in 120V and 230V
- With swivel arm



Benchtop model.

FEATURES & BENEFITS

- Single temperature measurement
- Digital display
- With swivel arm
- 2 yokes included

APPLICATIONS

- Bearings, gears, rings, couplings

PART NUMBERS:

HEATERS:

VHIY-G2-75-230VEU
 VHIY-G2-75-230VUS
 VHIY-G2-75-120VUS

ACCESSORIES:

VHIY-10x10x280 mm
 VHIY-14x14x280 mm
 VHIY-20x20x280 mm
 VHIY-30x30x280 mm
 VHIY-40x40x280 mm
 VHIY-50x50x280 mm
 VHIY-60x60x280 mm

Induction heating is a superior, fast and controlled heating method. It is a safer and more environmentally friendly alternative to traditional heating methods such as ovens or oil baths. These methods cause fumes or oil waste and are not recommended for personal health and safety. Do not heat with blow torches.



Timken® is registered trademark of The Timken Company
 www.timken.com
 © 2021 The Timken Company
 Ref: TDS03-21-GB

General		
Power rating 230V / 240V	3.7 kVA	
Power rating 120V	1.8 kVA	
Voltage/Amp*	230V/16A or 120V/15A	
Frequency	50/60 Hz	
Workpiece min./max. sizes		
	Metric	Imperial
Max. weight of workpiece	100 kg	220.46 lbs.
Min. bore diameter (vertical/horizontal)	30/72 mm	1.18/2.83"
Max OD	500 mm	19.69"
Max. workpiece width	180 mm	7.09"
Swing arm	Yes	
Pole Dimensions		
	Metric	Imperial
Pole dimensions	50x50 mm	1.97x1.97"
Pole height	185 mm	7.28"
Controls		
	Metric	Imperial
Max. temp	240° C	464° F
Max. time range	0-99 min.	
Auto power reduction	Yes	
Options		
	Metric	Imperial
Yokes (standard set)	20, 50 mm	0.79, 1.97"
Yokes (optional)	10, 14, 30, 40, 60	0.39, 0.55, 1.18, 1.57, 2.36"
Support for horizontal heating	Yes	
Mobile	No	
Temperature control	Yes	
Dimensions		
	Metric	Imperial
Dimensions	702x256x392 mm	27.64x10.08x15.43"
Package size	750x360x520 mm	29.53x14.17x20.47"
Heater weight (excluding yokes)	31 kg	68.34 lbs.
Miscellaneous		
Sound signal	Yes	
Temperature hold	Yes	
Demagnetizing, <2A/cm	Yes	
Thermal safety guard	Yes	
Magnetic temperature probe	1	
Temperature probe supplied	Yes	
Digital Display		
Temperature	Yes	
Time	Yes	
Error message	Yes	